

## VC- - NextColor Direct Gloss

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Code: VC-  
Product name: NextColor Direct Gloss

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Car spray can paint direct gloss color

Identified Uses	Industrial	Professional	Consumer
Body paint in spray can	✓	✓	✓
Uses Advised Against			
Uses other than those indicated.			

## 1.3. Details of the supplier of the safety data sheet

Name: E-COMIT srl  
Full address: Via G. Di Vittorio, 93-95 z.i. Terrafino  
District and Country: 50053 Empoli (Florence) Italy  
Tel.: +39 0571530262  
e-mail address of the competent person responsible for the Safety Data Sheet: info@e-comit.it

## 1.4. Emergency telephone number

For urgent inquiries refer to:

**UNITED KINGDOM - NHS (National Health Service):** For urgent help for people aged 5 or over use 111 (online). Call 111 for children under 5. Call 999 if it's a life-threatening emergency.

**IRELAND - Members of Public:** +353 (01) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) **Healthcare Professionals:** +353 (01) 809 2566 (24 hour service)

**AUSTRIA - Umweltbundesamt GmbH / Environment Agency** +43 664 6210336

**DENMARK - Danish Environmental Protection Agency** +45 72 54 40 00

**GERMANY - BfR Bundesinstitut für Risikobewertung / German Federal Institute for Risk Assessment** - +49-30-18412-0

**NETHERLANDS - National Poisons Information Center / University Medical Center Utrecht** +31 88 75 585 61

**ROMANIA - The Toxicology Information Center from the Emergency Clinic Hospital of Bucharest** - +40215992300

**LUXEMBOURG - Centre Antipoisons (BE) on behalf of Ministère-Direction de la Santé** +320 22649636/+352 24785551

**GREECE - Hellenic Republic Independent Authority for Public Revenue D.G. of the General Chemical State Laboratory Directorate of Energy, Industrial and Chemical Products** - +302106479250, +302106479450

## SECTION 2. Hazards identification

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

## VC- - NextColor Direct Gloss

## SECTION 2. Hazards identification ... / &gt;&gt;

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

## 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
<b>P501</b>	Dispose of contents / container to . . .
<b>P102</b>	Keep out of reach of children.
<b>P101</b>	If medical advice is needed, have product container or label at hand.
<b>P211</b>	Do not spray on an open flame or other ignition source.

**Contains:** XYLENE (MIXTURE OF ISOMERS)  
N-BUTYL ACETATE  
ACETONE  
ETHYLBENZENE

VOC (Directive 2004/42/EC) :

Special finishes - All types.

VOC given in g/litre of product in a ready-to-use condition : 726,92

Limit value: 840,00

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## VC- - NextColor Direct Gloss

## SECTION 3. Composition/information on ingredients

## 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>Dimethyl ether</b>		
INDEX 603-019-00-8	45 ≤ x < 47,5	Flam. Gas 1A H220, Press. Gas H280
EC 204-065-8		
CAS 115-10-6		
<b>N-BUTYL ACETATE</b>		
INDEX 607-025-00-1	13,5 ≤ x < 15	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
CAS 123-86-4		
REACH Reg. 01-2119485493-29		
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
INDEX 601-022-00-9	12 ≤ x < 13,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: 2000 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l
EC 215-535-7		
CAS 1330-20-7		
<b>ACETONE</b>		
INDEX 606-001-00-8	7 ≤ x < 8	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-2119471330-49		
<b>ETHYLBENZENE</b>		
INDEX 601-023-00-4	3 ≤ x < 3,5	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412 ATE Inhalation mists/powders: 1,5 mg/l
EC 202-849-4		
CAS 100-41-4		
REACH Reg. 01-2119489370-35		
<b>XYLENE</b>		
INDEX 601-022-00-9	2,5 ≤ x < 3	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l
EC 215-535-7		
CAS 1330-20-7		
REACH Reg. 01-2119488216-32		
<b>2-BUTOXYETHANOL</b>		
INDEX 603-014-00-0	0,6 ≤ x < 0,7	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315 LD50 Oral: 1746 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l
EC 203-905-0		
CAS 111-76-2		
REACH Reg. 01-2119475108-36		
<b>TOLUENE</b>		
INDEX 601-021-00-3	0 < x < 0,05	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9		
CAS 108-88-3		
REACH Reg. 01-2119471310-51		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.  
Percentage of propellants: 45,16 %

## SECTION 4. First aid measures

## 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.  
In case of more severe symptoms, ask for immediate medical aid.

**VC- - NextColor Direct Gloss****SECTION 4. First aid measures ... / >>**

**EYES:** Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

**INGESTION:** Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

**INHALATION:** Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**DELAYED EFFECTS:** Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

**4.3. Indication of any immediate medical attention and special treatment needed**

**IF SWALLOWED:** Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

**6.3. Methods and material for containment and cleaning up**

## VC- - NextColor Direct Gloss

**SECTION 6. Accidental release measures ... / >>**

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory references:

ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

**Dimethyl ether****Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
		mg/m3	ppm	
OEL	EU	1920	1000	

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,155	mg/l
Normal value in marine water	0,016	mg/l
Normal value for fresh water sediment	0,681	mg/l
Normal value for marine water sediment	0,069	mg/l
Normal value for water, intermittent release	1,549	mg/l
Normal value of STP microorganisms	160	mg/l
Normal value for the terrestrial compartment	0,045	mg/l

## VC- - NextColor Direct Gloss

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

## XYLENE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	327	mg/l
Normal value in marine water	327	mg/l
Normal value for fresh water sediment	1246	mg/l
Normal value for marine water sediment	1246	mg/l
Normal value of STP microorganisms	658	mg/l
Normal value for the terrestrial compartment	231	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					442		221	221
Skin					mg/kg		mg/kg	3182
								mg/kg

## XYLENE (MIXTURE OF ISOMERS)

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value for water, intermittent release	0,327	mg/l
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					442	442		221
Skin					mg/m3	mg/m3		221
								mg/kg/d

## VC- - NextColor Direct Gloss

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

## TOLUENE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
VLEP	ITA	192	50			SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	0,074	mg/l
Normal value in marine water	0,0074	mg/l
Normal value for fresh water sediment	1,78	mg/l
Normal value for marine water sediment	0,178	mg/l
Normal value for water, intermittent release	0,00378	mg/l
Normal value of STP microorganisms	0,84	mg/l
Normal value for the terrestrial compartment	0,313	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg/d				8,13
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg/d				384 mg/kg/d

## ETHYLBENZENE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
VLEP	ITA	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	13,7	mg/l
Normal value for marine water sediment	1,37	mg/l
Normal value for water, intermittent release	0,1	mg/l
Normal value of STP microorganisms	9,6	mg/l
Normal value for the terrestrial compartment	2,68	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,6		1,6 mg/kg bw/d				
Inhalation				15 mg/m3	293 mg/m3	293		77 mg/m3
Skin								180 mg/kg/d

## VC- - NextColor Direct Gloss

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

## 2-BUTOXYETHANOL

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	98	20	245	50	SKIN
VLEP	FRA	49	10	246	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

## Predicted no-effect concentration - PNEC

Normal value in fresh water	34,6	mg/kg
Normal value in marine water	3,46	mg/kg
Normal value for the terrestrial compartment	3,13	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
Inhalation	local	systemic	local	systemic	systemic	local	systemic	systemic
Skin								98 mg/kg 75 mg/kg

## ACETONE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	1210	500			
VLEP	FRA	1210	500	2420	1000	
VLEP	ITA	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

## Predicted no-effect concentration - PNEC

Normal value in fresh water	10,6	mg/l
Normal value in marine water	1,06	mg/l
Normal value for fresh water sediment	30,4	mg/kg
Normal value for marine water sediment	3,04	mg/kg

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
Oral	local	systemic	local	systemic	systemic	local	systemic	systemic
Inhalation				62 mg/kg/d	2420			1210 mg/m3
Skin				62 mg/kg/d	mg/m3			186 mg/kg/d

## VC- - NextColor Direct Gloss

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

## N-BUTYL ACETATE

## Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	241	50	723	150	
VLEP	FRA	241	50	723	150	
VLEP	ITA	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

## Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg/d
Normal value for marine water sediment	0,0981	mg/kg/d
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,0903	mg/kg/d

## Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	35,7 mg/m3	35,7 mg/m3	600 mg/m3	960 mg/kg	300 mg/m3	480 mg/kg
Skin		6 mg/kg/d				11 mg/kg bw/d		11 mg/kg bw/d

## Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

## Dimethyl ether

Derived no-effect level (DNEL)

type of application (use): worker

route of exposure: inhalation

health effects: chronic effects, systemic toxicity

DNEL value: 1,894 mg/m3

type of application (use): consumer

route of exposure: inhalation

health effects: chronic effects, systemic toxicity

DNEL value: 471 mg/m3

## XYLENE

Target: Occasional emission - Value: 0.327 mg/l

## XYLENE (MIXTURE OF ISOMERS)

Components with biological limit values:

1.5 g/g creatinine

Matrix: urine

Pickup time: at the end of the shift

Biological indicator of exposure: methylippuric acid

## TOLUENE

Components with biological limit values:

IBE (Italy):

0.02 mg/l

Matrix: blood

Collection time: first last shift of the working week

Biological indicator of exposure: toluene

0.03 mg/l

Matrix: urine

Pickup time: at the end of the shift

Biological indicator of exposure: toluene 0.03 mg/g creatinine

Matrix: urine

## VC- - NextColor Direct Gloss

## SECTION 8. Exposure controls/personal protection ... / &gt;&gt;

Pickup time: at the end of the shift  
Biological indicator of exposure: o-cresol

## ETHYLBENZENE

Components with biological limit values:

IBE (Italy): 0.7 g/g creatinine

Matrix: urine

Pickup time: f.t.f.s.l.

Biological indicator of exposure: mandelic acid + phenylglyoxylic acid

-

Matrix: end-expiratory air

Pickup time: not critical

## 2-BUTOXYETHANOL

Target: Occasional emission - Value: 463 mg/l

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

## HAND PROTECTION

None required.

## SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

## EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

## RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

## ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## Dimethyl ether

Skin protection: Wear work clothes with long sleeves and safety footwear for professional category I use (EN 344 standard).

Hand protection: Wear category I work gloves (EN 374 standard) made of latex, PVC or equivalent. To make the final choice of material, evaluate its degradation, breaking time and permeation.

Eye protection: Wear airtight protective glasses and a face shield in case there is the possibility of contact with the face (EN 166 standard).

Respiratory protection: In case of short and modest exposure, wear a filter for organic gases and vapors (EN 371 standard). In case of intense and long-lasting exposure, wear self-contained breathing apparatus (EN 137 standard).

General hygiene and protection measures: Wash hands before breaks and at the end of work. Do not eat, drink or smoke when using. Equip work environments with an eyewash system and a safety shower.

## SECTION 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	colourless	
Odour	characteristic of solvent	
Odour threshold	not determined	
Melting point / freezing point	not applicable	
Initial boiling point	> 35 °C	
Boiling range	not determined	
Flammability	flammable liquid	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	< 23 °C	
Auto-ignition temperature	400 °C	
Decomposition temperature		

## VC- - NextColor Direct Gloss

## SECTION 9. Physical and chemical properties ... / &gt;&gt;

Self-accelerating decomposition temperature (SADT)	not applicable	
pH	not determined	
Kinematic viscosity	not available	Concentration: 998 %
Dynamic viscosity	>20,5 mm <sup>2</sup> /sec a 40°	
Solubility	not determined	
Dissolution rate	insoluble in water	Reason for missing data:substance/mixture is non-soluble (in water)
Partition coefficient: n-octanol/water	not applicable	
Dispersion stability	not available	Reason for missing data:substance/mixture is non-soluble (in water)
Vapour pressure	not determined	
Density and/or relative density	0,84	
Relative vapour density	>Aria	
<b>Particle characteristics</b>		
<b>Median equivalent diameter</b>		
Remark:	Non applicabile	
<b>Size distribution</b>		
Remark:	Non applicabile	
<b>Dustiness</b>		
Remark:	Non applicabile	
<b>Specific surface area</b>		
Remark:	Non applicabile	
<b>Shape</b>		
Remark:	Non applicabile	

## 9.2. Other information

## 9.2.1. Information with regard to physical hazard classes

Information not available

## 9.2.2. Other safety characteristics

Information not available

## SECTION 10. Stability and reactivity

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

## Dimethyl ether

The substance is a highly flammable gas.

## TOLUENE

Avoid exposure to: light.

Avoid exposure to: light.

## 2-BUTOXYETHANOL

Decomposes under the effect of heat.

## ACETONE

Decomposes under the effect of heat.

## N-BUTYL ACETATE

Decomposes on contact with: water.

## 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## Dimethyl ether

Stable in normal conditions of use and storage.

The substance is stable under normal conditions of use and storage.

## VC- - NextColor Direct Gloss

## SECTION 10. Stability and reactivity ... / &gt;&gt;

## 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

## Dimethyl ether

The vapors of the substance can form an explosive mixture with air (formation of unstable peroxides).

## XYLENE

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

## XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

## TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

## ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

## 2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

## ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

## N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

## 10.4. Conditions to avoid

Avoid overheating.

## Dimethyl ether

Keep away from heat, sources of flame or sparks.

## 2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

## ACETONE

Avoid exposure to: sources of heat, naked flames.

## N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

## 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

## Dimethyl ether

Acids, oxidizing agents, powdered metals, oxygen and carbon monoxide.

## ACETONE

Incompatible with: acids, oxidising substances.

## N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

## 10.6. Hazardous decomposition products

## Dimethyl ether

Thermal decomposition of the substance produces toxic vapors (carbon oxides, formaldehyde, methanol).

## ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

## 2-BUTOXYETHANOL

May develop: hydrogen.

## ACETONE

May develop: ketenes, irritant substances.

## VC- - NextColor Direct Gloss

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

## XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

## XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

## TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

## ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

## N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

## XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

## TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

## ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesi). Is irritating for skin, conjunctiva and respiratory tract.

## N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

## XYLENE

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

## XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the

## VC- - NextColor Direct Gloss

## SECTION 11. Toxicological information ... / &gt;&gt;

concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

## TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

## N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	3,7 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

## XYLENE

LD50 (Dermal):	> 1700 mg/kg Rabbit
LC50 (Inhalation vapours):	5000 ppm/4h Rat
ATE (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

## XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal):	2000 mg/kg Rabbit
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	27,541 mg/l/4h Rat
ATE (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

## TOLUENE

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

## ETHYLBENZENE

LD50 (Dermal):	15400 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,6 mg/l/1h Rat
ATE (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

## 2-BUTOXYETHANOL

LD50 (Dermal):	6411 mg/kg Ratto
LD50 (Oral):	1746 mg/kg Ratto
LC50 (Inhalation gas):	450 ppm/4h Ratto
ATE (Inhalation mists/powders):	0,501 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

## N-BUTYL ACETATE

LD50 (Dermal):	> 10000 mg/kg Rabbit
LD50 (Oral):	> 8000 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

## Dimethyl ether

LC50 Inhalation rat 164,000 ppm respiratory, anesthetic, central nervous system depressant effects, narcosis, cardiac irregularity, coma.

## Skin corrosion/irritation:

Based on expert assessments, the substance is not expected to cause skin irritation (not tested on animals). Contact of the substance in liquid phase with the skin can cause serious cold injuries.

## Serious eye damage/eye irritation:

Based on expert assessments, the substance is not expected to cause eye irritation (not tested on animals). Contact of the substance in liquid phase with the eyes can cause serious cold injuries.

## Respiratory or skin sensitization:

**VC- - NextColor Direct Gloss****SECTION 11. Toxicological information ... / >>**

Based on expert assessments, the substance is not expected to have sensitizing effects (not tested on animals).

Repeated dose toxicity:

Inhalation studies conducted on rats have not shown significant toxicological effects.

Germ cell mutagenicity:

Tests conducted on cultures of bacterial or mammalian cells have not shown mutagenic effects.

Carcinogenicity

Animal testing has not shown any carcinogenic effects.

Reproductive toxicity: No reprotoxic effects.

**XYLENE (MIXTURE OF ISOMERS)**

ATE (Vapour inhalation): 11 mg/l estimated from table 3.1.2 of Annex I of CLP (data used to calculate the estimate of the acute toxicity of the mixture)

**2-BUTOXYETHANOL**

**OBSERVATIONS ON MAN:**

probable lethal oral dose: 50-500 mg/kg.

Following repeated and/or prolonged exposures causes headaches, drowsiness, weakness, stuttering, tremor, blurred vision, albuminuria and spinal cord damage bone.

**SKIN CORROSION / IRRITATION**

Causes skin irritation

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye irritation

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**XYLENE**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**XYLENE (MIXTURE OF ISOMERS)**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**TOLUENE**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

**ETHYLBENZENE**

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

May cause respiratory irritation

May cause drowsiness or dizziness

**STOT - REPEATED EXPOSURE**

## VC- - NextColor Direct Gloss

**SECTION 11. Toxicological information ... / >>**

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Dimethyl ether

LC50 (48 h) daphnia magna 755.549 mg/l

Dimethyl ether

LC50 - for Fish

> 4000 mg/l/96h trota iridea

EC50 - for Crustacea

> 4000 mg/l/48h daphnia magna

ETHYLBENZENE

LC50 - for Fish

4,2 mg/l/96h oncorhynchus mykiss

EC50 - for Crustacea

1,8 mg/l/48h

Chronic NOEC for Crustacea

1 mg/l

Chronic NOEC for Algae / Aquatic Plants

3,4 mg/l 72h

2-BUTOXYETHANOL

LC50 - for Fish

1474 mg/kg Pesci

EC50 - for Crustacea

1550 mg/l/48h Dafnie

EC50 - for Algae / Aquatic Plants

911 mg/l/72h Alghe

N-BUTYL ACETATE

LC50 - for Fish

100 mg/l/96h Lepomis macrochirus

EC50 - for Algae / Aquatic Plants

674,7 mg/l/72h Desmodemus subspicatus

**12.2. Persistence and degradability**

XYLENE

Solubility in water

100 - 1000 mg/l

Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

Solubility in water

100 - 1000 mg/l

Rapidly degradable

TOLUENE

Solubility in water

100 - 1000 mg/l

Rapidly degradable

ETHYLBENZENE

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

ACETONE

Rapidly degradable

N-BUTYL ACETATE

Solubility in water

1000 - 10000 mg/l

## VC- - NextColor Direct Gloss

## SECTION 12. Ecological information ... / &gt;&gt;

## 12.3. Bioaccumulative potential

XYLENE	
Partition coefficient: n-octanol/water	3,12
BCF	25,9

XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3,12
BCF	25,9

TOLUENE	
Partition coefficient: n-octanol/water	2,73
BCF	90

ETHYLBENZENE	
Partition coefficient: n-octanol/water	3,6

2-BUTOXYETHANOL	
Partition coefficient: n-octanol/water	0,81

ACETONE	
Partition coefficient: n-octanol/water	-0,23
BCF	3

N-BUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3

## 12.4. Mobility in soil

XYLENE	
Partition coefficient: soil/water	2,73
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2,73
N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3

## 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

## 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

## 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

## 14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1950

## VC- - NextColor Direct Gloss

## SECTION 14. Transport information ... / &gt;&gt;

## 14.2. UN proper shipping name

ADR / RID: AEROSOLS  
IMDG: AEROSOLS  
IATA: AEROSOLS, FLAMMABLE

## 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



## 14.4. Packing group

ADR / RID, IMDG, IATA: -

## 14.5. Environmental hazards

ADR / RID: NO  
IMDG: not marine pollutant  
IATA: NO

## 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 lt	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 lt	
IATA:	Cargo:	Maximum quantity: 150 kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

## VC- - NextColor Direct Gloss

## SECTION 15. Regulatory information ... / &gt;&gt;

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes - All types.

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Gas 1A</b>	Flammable gas, category 1A
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Press. Gas</b>	Pressurised gas
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H280</b>	Contains gas under pressure; may explode if heated.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H331</b>	Toxic if inhaled.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

## VC- - NextColor Direct Gloss

## SECTION 16. Other information ... / &gt;&gt;

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**VC- - NextColor Direct Gloss****SECTION 16. Other information ... / >>****CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

09.